

**589843 (MCIDAAJODM)**

Induction Top, 4 zones, one-side operated - MARINE

Main Features

- Fast deployment with full heating power immediately.
- Low heat dissipation to the kitchen.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Pans can easily be moved from one area to another without lifting.
- The smooth glass-ceramic surface can be quickly and easily cleaned, thus providing maximum hygiene.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal-covered knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- 9 power levels.

Construction

- IPX5 water resistance certification.
- Control light for each zone.
- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Rolling rack included

Sustainability

- This model is compliant with Swiss Energy Efficiency Ordinance (730.02).




Optional Accessories

PNC Code	Description
Cleaning solutions	
910601	Scraper for cook tops
Connection and endrail kits	
912502	Connecting rail kit, 900mm
913111	Endrail kit, flush-fitting, left
913112	Endrail kit, flush-fitting, right
913202	Endrail kit (12.5mm) for thermaline 90 units, left
913203	Endrail kit (12.5mm) for thermaline 90 units, right
913227	T-connection rail for back-to-back installations without backsplash (to be ordered as S-code)
913251	Endrail kit, (12.5mm), for back-to-back installation, left
913252	Endrail kit, (12.5mm), for back-to-back installation, right
913255	Endrail kit, flush-fitting, for back-to-back installation, left
913256	Endrail kit, flush-fitting, for back-to-back installation, right
Filters	
913666	Filter W=1000mm
Shelves	
912528	Portioning shelf, 1000mm width
912558	Portioning shelf, 1000mm width
912581	Folding shelf, 300x900mm
912582	Folding shelf, 400x900mm
912589	Fixed side shelf, 200x900mm
912590	Fixed side shelf, 300x900mm
912591	Fixed side shelf, 400x900mm
Wall mounting kits	
913654	Wall mounting kit top - TL85/90 - Factory Fitted
Other accessories	
052884	S04 Glasses & Hard Surfaces Cleaner, 6 x 750ml bottles



Technical specifications

Electric	
Supply voltage:	440 V/3 ph/50/60 Hz
Total Watts:	20 kW
Key Information:	
External dimensions, Width:	1000 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	250 mm
Net weight:	94 kg
Configuration:	One-Side Operated;Top
Front Plates Power:	5 - 5 kW
Back Plates Power:	5 - 5 kW
Front Plates dimensions:	340x370 340x370
Back Plates dimensions:	340x370 340x370
Induction Top Dimensions (width):	1000 mm
Induction Top Dimensions (depth):	900 mm
Sustainability	
Current consumption:	27.3 Amps



EI = Electrical inlet (power)
EQ = Equipotential screw



Find out more:
ISO Certificates
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.