

PDR 908 [EL MAR 2 AC 208-240V 60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 8.0 kg.



- Drum volume 130.00 l, load size 8.0 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry

EAN: 4002516216896 / Material number: 11251140 /  
Old Material Number: 52908489MAR

## Construction type and version

|                                |                            |
|--------------------------------|----------------------------|
| Construction type              | Front loader               |
| Range                          | Performance Plus           |
| Front                          | Stainless steel            |
| Side panels                    | Powder-coated, lotus white |
| Fascia color                   | Stainless steel            |
| Load in kg                     | 8,0                        |
| Drum volume in l               | 130,00                     |
| Drying system                  | Exhaust air                |
| Door opening [Ø] in mm         | 370                        |
| Door opening angle in degrees  | 167                        |
| Door hinge                     | left                       |
| Stainless steel honeycomb drum | Yes                        |

## Application

|                           |   |
|---------------------------|---|
| Suitable for offshore use | • |
| Suitable for marine use   | • |

## Performance data

|                                                                                                      |      |
|------------------------------------------------------------------------------------------------------|------|
| Maximum evaporation capacity in l/hour                                                               | 3,7  |
| Specific energy consumption in kWh/kg                                                                | 0,49 |
| Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW | 0,49 |
| Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture a | 0,41 |
| Programme duration in min.                                                                           | 62   |
| Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes     | 62   |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in | 57   |

## Control system

|                                             |                              |
|---------------------------------------------|------------------------------|
| Control system                              | M Touch Flex                 |
| Programmability                             | programmable                 |
| User interface                              | Residual moisture controlled |
| Max. delay start in h                       | 24                           |
| Time left display                           | •                            |
| Programme sequence indicator                | •                            |
| Language can be selected easily at any time | •                            |

## Standard electrical connection

|                              |                  |
|------------------------------|------------------|
| Heating type                 | Electric         |
| Electrical connection        | 2~ 208-240V 60HZ |
| Electric heater rating in kW | 3,03 - 4,04      |
| Total connected load in kW   | 3,40 - 4,30      |
| Fuse rating in A             | 30               |

## Dimensions and weight of dryer

|                                         |     |
|-----------------------------------------|-----|
| External dimensions, height in mm       | 850 |
| External dimensions, width in mm        | 606 |
| External dimensions, depth in mm        | 717 |
| External dimensions, gross height in mm | 940 |
| External dimensions, gross width in mm  | 660 |

PDR 908 [EL MAR 2 AC 208-240V 60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 8.0 kg.



EAN: 4002516216896 / Material number: 11251140 /

Old Material Number: 52908489MAR

|                                        |      |
|----------------------------------------|------|
| External dimensions, gross depth in mm | 820  |
| Net weight in kg                       | 72,0 |
| Gross weight in kg                     | 78   |
| Maximum floor load in N                | 920  |

#### Emissions data

|                                                |                     |
|------------------------------------------------|---------------------|
| Emission sound pressure level in the workplace | ≤70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h         | 0,76                |

#### Features

|                                 |   |
|---------------------------------|---|
| Intelligent drum reversal       | • |
| Axial airflow                   | • |
| Large-surface filter            | • |
| PerfectDry                      | • |
| SoftLift drum ribs              | • |
| Low temperature function        | • |
| Communication slot              | • |
| Drying basket (optional)        | • |
| Drum lighting                   | • |
| Machine-independent accessories | • |

#### Efficiency

|                     |    |
|---------------------|----|
| Recycling rate in % | 95 |
|---------------------|----|

#### Connection options

|                                                      |   |
|------------------------------------------------------|---|
| Payment system (optional)                            | • |
| Optical interface for service access                 | • |
| Peak-load negotiation / energy management (optional) | • |
| LAN/WiFi module (optional)                           | • |
| WiFiConn@ct                                          | • |

#### Standards, test certificates and symbols

|                                              |   |
|----------------------------------------------|---|
| WEEE                                         | • |
| Lloyd's Register                             | • |
| Complies with Machinery Directive 2006/42/EC | • |